

# UEDU SWAKOP, 2019

#### **Presented by: Johans Haarhoff**





#### AGENDA

- Introduction: Who are we?
- Recent Developments: DV Power, Gossen
- MV and HV testing options, both On-Line and Off-Line as a means of Preventative Maintenance

Product

Sales

Repair and

Calibration

Training

Centre

and Auditina

Services

- Closer Look: Transformer, MV Cable Testing
- Questions




# **WHO ARE WE**

- ▲ Incorporated in 1982
- ▲ International Ties
- ▲ Projects in Guatemala, Oman and Ireland
- ▲ Specialist projects:
  - Oil Cable Leak location Sandton: Unique Technology
  - Off Line Cable Diagnostics TD and PD
  - On Line Diagnostics Eskom 400kV cables
  - Overhead Line Fault location Eskom, Nampower, EDM, BPC
  - Transformer Rewind Test Facility Rotek: 800MVA
  - Motor Rewinding Actom
  - Traction Motor facilities Transnet





#### **INTERNATIONAL TIES**



Product

Sales

Training


Centre

Repair and

Calibration

H.V. TEST (PTY) LTD Leaders in High Voltage Test Equipment

#### **INTERNAL DIVISIONS OF HV TEST**







## **RECENT DEVELOPMENTS**

We recently added the following Manufacturers to our stable:

- DV Power (Sweden)
- Gossen Metrawatt (Germany)





# **DV POWER**

- Swedish Company
- 3 Year Warranty
- Battery Testing
- Circuit Breakers
- Transformer / Motor
- CT's and VT's
- Handheld Devices





#### **GOSSEN METRAWATT**

- German based Company
- Quality Multimeters
- 5kV and 10kV Insulation
- Substation Earthing
- 3 Phase Socket Factories
- Solar Panel Efficiency



Commissioning

Services

Repair and

Calibration

Training


Centre

Product

Sales




# **HV TEST PRIMARY DIVISIONS**



- Thumping / Surge Testing
- SSG500, SSG1500
- 16kV, 11kV networks
- 32kV, 11-33kV networks
- 500J, 1100J 3000J





Product Sales

Commissioning and Auditing Services

Training Centre Repair and Calibration

- Wheatstone /
- Murray Bridge
- Shirla
- Great for 0 Ohm faults
- Build into the Shirla









- Pre-Location
- IRG2000 / IRG4000
- TDR
- ICM
- SIM / ARC Reflection









- Pin Pointing
- Protrac
- Bluetooth
- Receiver
- Ground Microphone
- Headset







- Cable Tracing
- Ridgid SR-24
- Transmitters 10W, 5W
- 4" Clamp Live Cables
- GPS marking location
- Bluetooth to Android device





Product

Sales



Repair and


Calibration

Training

Centre



- Cable Identification
- EZID
- Phasing is also possible
- Must have access to one side
- Best to ID dead ( Tx







#### Cable Spiking

- Schermer (Utilities)
- Picoup400 (Mines)
- Hydraulic as optional
- This saves lives !!
- Remote firing of the



Repair and

Calibration

Training

Centre





- Sheath Fault Location
- Shirla
- 5kV DC Test
- Spikes





Sales

Repair and

Calibration

Centre





- PFT Oil Leak Location
- The oil cable is "Tagged"
- A GC is used to locate the leaking gas
- De-gassifier Trailers





Repair and

Calibration

Training

Centre

Product

Sales



- Pressure Testing
- DC
- AC, 50Hz
- VLF, 0.1Hz
- Testing the insulation
- Test according to the std.







- DC Hipot
- PGK50
- Still used on PILC cable
- Cheaper Equipment
- Meaningless on AC cables







#### • AC 50Hz

- Equipment is large
- Expensive
- 44kV cables and up
- Back energise on open-circuit



Variable Frequency, 265 kV, 22 MVA





- VLF 0.1Hz
- Using VLF or 0.1Hz pure sine
- Only test for XLPE up to 33kV
- Commissioning
- Maintenance
- Joints and Terminations









#### • Cable Diagnostics

- Combine a Tan-Delta test
- Footprint
- Indication of deterioration
- PD Test



Repair and

Calibration





- Online Tan Delta
- TD Guard
- absolute Tan-δ values in on-line permanent monitoring
- Innovative instrument for Capacitance, Tan-δ and Δtan-δ recording, storage & processing





- Online Partial Discharge
- PD detection at 50Hz
- Can't increase the voltage
- Cable Voltage not Relevant








- Offline Tan Delta
- Tests are performed at 0.1Hz, Voltage is manually controlled
- Foot printing and cable deterioration









- Offline Partial Discharge
- Inception and Extinguishing voltage









Jointing- and Splicing tools





- Turns Ratio
- Comparing the ratio can easily show faults
- Field or Maintenance Test
- 1 Phase or 3 Phase Testing







Commissioning

Services

Repair and

Calibration

Training

Centre

Product

Sales

- Winding Resistance
- DC Resistance Test
- Temperature Measurement Possible
- 1 Phase or 3 Phase







Product Sales

g Training Centre Repair and Calibration

- Tap Changer
- Dynamic Resistive plot of the taps
- 3 Phase option with Winding



Repair and

Calibration

Training

Centre

Product

Sales





- Insulation Resistance
- Metriso Prime10
- 5kV, 10kV, 15kV options
- PI, DAR
- Megger



Product

Sales

Repair and

Calibration

Training

Centre



- Variac and Multimeter
- Nameplate verification
- % Impedance
- Open & Short Circuit





Repair and

Calibration

Training

Centre

Product

Sales

- Tan Delta
- Bushings
- Tank
- 2 Separate units
- 1 Dedicated TD unit







- FRA
- Verify that the windings did not move around during transport
- Tests is performed before on loading
- Repeated after installation
- Sweep: 5Hz to 45MHz



Commissioning

Services

Training

Centre

Repair and

Calibration

Product

Sales




- Oil Dielectric
- 60kV, 75kV, 80kV, 100kV
- Water in Oil (Karl Fischer)











#### **POWER TRANSFORMERS**

#### • Oil Tan Delta







#### **POWER TRANSFORMERS**

#### • Transformer Test Bay





Product Sales Commissioning and Auditing Services Training Centre Repair and Calibration

# **CIRCUIT BREAKER**

- Speed / Timing Tests
- Indoor / Outdoor
- 3 Channels / 1 Break / Ph
- 6 Channels / 2 Break / Ph
- 12 Channels / 4 Break / Ph
- On-Line







# **CIRCUIT BREAKER**

- Static Resistance
- CAT61 or CAT-P
- Typical 10A, 50A, 100A, 200A
- Up to 800A
- Loose equipment or build in to the Circuit Breaker Analyser
- Handheld up to 30(





Product Sales and Auditing Services

Training Centre Repair and Calibration

# **CIRCUIT BREAKER**



- Minimum Pick Up
- POB30
- Test to verify that the breaker coils will still fire even at 70% of station battery voltage
- Variac might damage the coil during the ramping





- Earth Resistance Testing
- Soil Resisivity

STS 5000 isa

- 4-Wire Method
- Step and Touch (current)



Product

Sales

「二、四一で

Repair and


Calibration

Training

Centre



- Disturbance Recording
- 9, 18, 36 Analogue Channels
- 32, 64, 96, 128 Digital Channels
- IEC 61850



Repair and

Calibration

Training

Centre

Product





- Power Quality
- IEC 61000-4-30 Class A
- 19" Rack / Portable
- PQ and DFR







- Voltage Detection
- Contact
- **Non-Contact**
- Up to 765kV



Sales

Training

Centre

Calibration





- AC Hipot
- Busbar Testing
- 50Hz Test
- 3mA per panel
- Consider the current







- Primary Injection
- Customer has to specify the max current
- 200A is still regarded as secondary injection
- 12000A or more







Training

Centre

Repair and

Calibration

Commissioning

Product

- CT Mag Curve, Ratio and Polarity
- Single or multiple tap











- Partial Discharge Monitoring
- Handheld
- Permanent monitor of GIS and transformers
- Cloud Storage








Product Sales Commissioning and Auditing Services

Training Centre Repair and Calibration






For use **on very HV overhead lines**, both T and R shall obligatorily be equipped with their specific probe extension (white).





For use **in switchgears**, both T and R shall obligatorily be equipped with their safety electrode extension (grey).






- Phasing Sticks
- Switchgear









- Recloser Test Bay
- 0 7.50, 2500A
- 19kVA, 47kVA







Product

Sales

Repair and

Calibration

Training

Centre

- Vacuum Bottle
- 40kV, 60kV



# **PROTECTION RELAYS**

- Single Phase Injection
- CDG Electromechanical relay
- High VA relays
- Manual Testing



Repair and

Calibration

Training

Centre

Product



# **PROTECTION RELAYS**

- Three Phase Injection
- 3 Currents 3 Voltages
- 3 Currents 4 Voltages
- 6 Currents 4 Voltages
- 6 Currents 6 Voltages
- IEC 61850
- Transcope



Product

Sales

Commissioning

Services

Repair and

Calibration

Training

Centre



#### BATTERIES


- Battery Resistance
- Battery Resistance
- Test a string of cells
- Record results to a database







#### BATTERIES



BLU + BXL to battery connection diagram

- Battery Discharge
- Additional load units available



Repair and

Calibration

Training

Centre

Product



- Distance To Fault Recorders (NAMPOWER)
- FL8 and FL1
- For Lines of voltages 66kV and up
- +/- 120m accuracy
- Software automatically calculates distance to fault
- Save money on costly Line investigations





- Earth Tower Footing Resistance
- ER25K
- Measuring earth resistance of electrical pylons
- High frequency measurement current (25kHz)





Commissioning

Services

Repair and

Calibration

Training

Centre

Product

- Surge Arrestor
- SCAR10
- True rms of the total current.
- Peak value of the total current.







Product

Sales

Repair and

Calibration

Training

Centre



- Up to 765kV
- Voltage Detection





- PGK50
- AC / DC Pressure Testing





# **MOTORS & GENERATORS**

- Resonance
- We can provide
- 50Hz pressure test
- PD Test
- Recent work includes Ingula, Drakensberg



Repair and

Calibration

Training

Centre

Product



- Multimeters
- Entry Level
- Mid Range
- High End
- Calibrators
- 1kV Insulation Testers













- Clamp-on Meters
- Non-Invasive Current Measurement



- Photovoltaic Meters
- PV condition
- Insulation measurement
- Polarity testing
- Ground fault testing
- Protective conductor continuity







- Portable Appliance Testers
- Testing for N-PE reversal
- Tripping test with nominal residual current, trip time measurement
- Earthing Resistance RE
- Selective Earthing Resistance RE
- Earth Loop Resistance RE loop
- Soil Resistivity Rho





Commissioning

Services

Repair and

Calibration

Training

Centre

Product



- Substation Rescue Equipment
- Electrical safety kit 25kV 36kV







Repair and

Calibration

Training

Centre

Product

- Tools for Explosive Environment
- Voltage, Resistance, Current, Frequency
- Intrinsically safe electric circuits up to 1000 V
- CAT IV, 1000 V



Training

Centre

Repair and

Calibration

CE

Services

Product





- Live Line Testing Bays
- 1 or 2 Gloves
- Complete Bay



H.V. TEST (PTY) LTD Leaders in High Voltage Test Equipment

missioning LAuditing Centre ervices

Product

Sales

Repair and Calibration

# **TRANSFORMER & CABLE TESTING**

Reasons for Preventative Maintenance Testing:

- Extend the live of the asset
- Prevent unexpected outages
- Prevent catastrophic failures





#### VANDERBIJL, MARCH 2019



Product Sales ommissioning and Auditing Services

Training Centre Repair and Calibration

# **TRANSFORMER TESTING**

 Different tests have been implemented for different scenarios. They consist of routine testing, type testing and special testing. We will be looking at a summary of routine testing.

Product

Sales

Repair and

Calibration

Training

Centre

Services

 Routine tests are tests required for each individual transformer.



## **TRANSFORMER TESTING**

Commissioning

Services

Training

Centre

Repair and

Calibration

Product

Sales

- Test Standards:
- IEC 60076 -1, IEC 60076 -2, IEC 60076 -3,
- IEC 60076 -4, IEC 60076 -5, IEC 60076 -6,
- IEC 60076 -7, IEC 60076 -8, IEC 60076 -9,
- IEC 60076 -10, IEC 60076 -11



#### **Transformer Ratio Test**

• The ratio test ensures that the transformer windings have the proper turns to produce the voltages required. The ratio is a measure of the voltage applied to the primary terminals to the voltage measured at the secondary terminals.



Product Sales

and Auditing Services

Training Centre Repair and Calibration

**Vector Group and Polarity** 

• The polarity and vector group of the transformer must be tested and checked to match the vector group on the nameplate.





#### Impedance Test

- Also known as, Load or short circuit test.
- This test is performed to ensure the stated nameplate impedance and the measured transformer impedance match.



and Auditing Services

Training

Centre

Repair and Calibration

No-Load Test (Magnetisation)

• This test verifies the design and core performance by indication of the no load current drawn by the transformer.

Product

Sales

Repair and

Calibration

Training

Centre

and Auditina

Services

 The magnetisation current is a factor of losses in the electric circuit, losses in the magnetic circuit, and losses in the dielectric circuit.



#### Winding Resistance

• The winding resistance is performed to determine the resistance of the conductors in the transformer winding, and the tap-changer contacts resistances.



Product Sales

Commissioning and Auditing Services

Training Centre Repair and Calibration

**Tap-change Continuity** 

• The tap-changer contacts are tested for electrical continuity during tap-changing.

Product

Sales

Repair and

Calibration

Training

Centre

and Auditina

Services

 By applying a constant current while tapping the tester looks for open circuit transients during tap-changing.



Insulation Resistance Test (Popular Test)

• The purpose of this DC test indicates the degree of dryness of the insulation and ground circuits that may exist.





Dielectric Absorption (DA) and Polarization Index (PI)

- Evaluating the windings for the following:
  - o Build up of dirt or moisture.
  - o Gradual deterioration of the insulation (comparing results)

Commissioning

and Auditina

Services

Training

Centre

Repair and

Calibration

Product

Sales

o Suitability for operation.



Tan Delta Test on the transformer and the Bushings (where possible)

• The Tan Delta is a measure of the insulation loss

Product

Sales

Repair and

Calibration

Training

Centre

and Auditina

Services

• The bushings of the transformer are tested before fitting and/or transport



Commissionina

Services

Training

Centre

Repair and

Calibration

Product

Sales

Frequency Response Analysis (FRA) Test

 This technique is designed to detect winding shifts through non-destructive methods, before and after transport of the transformer



#### **Other Tests**

- Oil Testing Dielectric Strength
- Dissolved Gas Analysis
- Water Content
- Acidity

#### THESE ARE USUALLY SENT AWAY TO A LAB.



Product Sales Commissioning and Auditing Services

Training Centre Repair and Calibration

- Introduction
- The new Standard (SANS 10198-13:2016) overview
- Testing On Site



Services

Repair and

Calibration

Training

Centre

Product

Sales



#### **Recommended methods of Testing**

- 50 Hz Testing
- Very Expensive



#### • Very low Frequency (VLF) Testi






Repair and Calibration

#### **VLF Wave Shapes:**

Cosine Rectangular Waveform




• **Disadvantage:** No diagnostic possible





#### **VLF Wave Shapes:**

Sinusoidal Wave form



- Wave Shape are equally positive and negative.
- Advantage: Diagnostic possible





**Direct Current (DC) Testing:** 

SANS 10198: 2016 Part 13 excludes DC Testing "D.C. Overvoltage is likely to cause irreversible damage on aged cables"

- Why exclude DC from PILC Cables?
  - Because we are using "solid dielectrics" (Heat <u>Shrink)</u> on joints or terminations (almost 90%)





#### Summary of Changes (SANS 10198-13:2016):

- Incorporates all cables up to less than 33kV
  - PILC screened and bolted
  - XLPE
  - EPR
  - Bundle
  - PVC
- Additional Test: Conductor Resistance
- Insulation Resistance Test : before and after testing





#### **Recommended Test Requirements (Commissioning)**


- Insulation Resistance Test (DC 1000V)
- Conductor Resistance Test (DC)
- Overvoltage Test
- Outer Sheath Test
- Diagnostic Tests: (fingerprinting & future trending)
- Insulation Resistance Test (DC 1000V)





#### **Conductor Resistance Test:**

- This is a new requirement (check Joints).
- Use two cores, loop for end, and divide result by 2
- Instrument to use is the "Ductor" 4 wire method
- Aberdare and CBI Cable Brochures provide conductor resistance tables



**Example:** 10km of 240mm2 Cable is 7.8 Ohm



 $C_1$  and  $C_2$  $P_1$  and  $P_2$ 

current lead connections potential lead connections






#### **Cable Sheath Testing:**

After overvoltage testing cable sheath testing is recommended:

- 5 kV for 1 minute (Recommended)
- NB: Lift the far end of the earth bar!
- Roughly guide 1 mA per km test source



#### **Overvoltage Commissioning Testing:**

#### Newly Installed Individual screened (Radial field) (cores) on M.V. Cables

1	2	3	4
Cable operating voltage kV	VLF Test voltage sine kV	VLF Test voltage cosine rectangular kV	Power-frequency test voltage kV
6.6	11	16	8
11	19	27	13
22	38	54	25
33	57	80	38
NOTE 1 The voltages given are root equal to the peak voltage. NOTE 2	mean square (r.m.s.) values	. The r.m.s. value of a cosine	rectangular voltage is
	vitchgear) connected to the	tations are placed on the max cable, a reduced voltage for a	

Table 1 – Commissioning test voltages for newly installed individually screened MV cables

#### Test time 60 minutes/core

Notes:

- Only for individual screen cables (radially stressed)
- This table applies to XLPE, EPR and PILC (non-belted and individual screen cables).
- More than one core can be tested simultaneously provided the test set has the capacity.





#### **Overvoltage Maintenance Testing:**

#### Individual screened (Radial field) (cores) on M.V. Cables

Table 7 – Commissioning test voltages for individually screened MV cables

1	2	3	4
Cable operating voltage kV	VLF Test voltage sine kV	VLF Test voltage cosine rectangular kV	Power-frequency test voltage kV
6.6	8	11	5
11	13	18	9
22	25	35	17
33	38	54	25

#### NOTE 1

The voltages given are root mean square (r.m.s.) values. The r.m.s. value of a cosine rectangular voltage is equal to the peak voltage.

#### NOTE 2

NOTE 3

Where the test levels cannot be achieved or where limitations are placed on the maximum test voltage by the equipment (for example, switchgear) connected to the cable, a reduced voltage for an extended duration may need to be considered and agreed to.

The test used for maintenance are two-thirds (2/3) of the test voltages for newly installed cables.

#### Notes:

- Test time is 60 minutes/core
- Only for individual screen cables (XLPE + PILC)
- Not Belted PILC cable
- Multiple cores can be tested simultaneously provided the test set has the capacity





#### **Diagnostic Testing (TD)**

- Not specified as mandatory but recommended
- TD is a excellent and easy test
  - Simple and today part of Pressure Test Set
  - Very meaningful for ageing cables
  - Excellent "Fingerprint"
  - Temperature, site conditions, moisture sensitive
  - Water trees are only detected by T.D. (not P.D.)
  - TD is an indication of the TD of the <u>whole cable</u>
  - Unlike P.D. location of poor T.D. source is not possible





#### **Diagnostic Testing (PD)**

- Not specified as mandatory but recommended
- PD provides location of source of discharge
- PD requires highly skilled technician with experience





#### **TD Variables**

#### Tan Delta (TD)

Calculate the TD using the average value calculated at U<sub>o</sub>

#### Delta tan delta (DTD)

- Calculate the DTD using the average values calculated at  $0.5 \rm U_{o}$  and  $1.5 \rm U_{o}$ 

#### Tan delta stability (TDS)

• Calculate the TDS using the following formula at U<sub>o</sub>

• 
$$TDS = \sqrt{\frac{\sum (TD - \overline{TD})^2}{(n-1)}}$$

- TD : a measured TD point in the test series
- $\overline{TD}$  : the average tan delta of the series
- $n_{\rm c}$  : the number of TD points in the test series





#### **TD Testing (Commissioning)**

Table 3 – Guidelines for the condition assessment of cables based on 0,01 Hz VLF-TD, DTD and TDS for newly installed XLPE cables<sup>a</sup>

1	2	3	4
Condition Assessment	TD at Uo [10 <sup>-3</sup> ]	DTD [10 <sup>-3</sup> ]	TDS at Uo [10 <sup>-3</sup> ]
No action required	<2.5	<0.6	<0.2
Further study advised	2.5 to 5	0.6 to 1	0.2 to 0.5
Action required	>5	>1	>0.5
<sup>a</sup> XLPE cables in operation for less than five years			

Table 5 – Guidelines for the condition assessment of cables based on 0,01 Hz VLF-TD, DTD and TDS for newly installed PILC Cables<sup>a</sup>

1	2	3	4
Condition Assessment	TD at Uo [10 <sup>-3</sup> ]	DTD [10 <sup>-3</sup> ]	TDS at Uo [10 <sup>-3</sup> ]
No action required	<25	-20 to 20	<0.5
Further study advised	25 to 50	-20 to -50	0.5 to 1
		or	
		20 to 50	
Action required	>50	>-50 or >50	>1
<sup>a</sup> PILC cables in operation	n for less than five years		



Product Commissioning Sales Services

Training Centre Repair and Calibration

#### **TD Testing (Maintenance)**

Table 4 – Guidelines for the condition assessment of cables based on 0,01 Hz VLF-TD, DTD and TDS for aged (in service) XLPE Cables

1	2	3	4
Condition Assessment	TD at Uo [10 <sup>-3</sup> ]	DTD [10 <sup>-3</sup> ]	TDS at Uo [10 <sup>-3</sup> ]
No action required	<2.5	<3	<0.5
Further study advised	2.5 to 25	3 to 30	0.5 to 1
Action required	>25	>30	>1

Commissioning

Services

Trainina

Centre

Repair and

Calibration


Product

Sales

Table 6 – Guidelines for the condition assessment of cables based on 0,01 Hz VLF-TD, DTD and TDS for aged (in service) PILC Cables

1	2	3	4
Condition Assessment	TD at Uo [10 <sup>-3</sup> ]	DTD [10 <sup>-3</sup> ]	TDS at Uo [10 <sup>-3</sup> ]
No action required	<50	-35 to 10	<0.5
Further study advised	50 to 200	-35 to -50	0.5 to 1
		or	
		10 to 50	
Action required	>200	>-50 to 50	>1









#### Thank you, any Questions?



